



Textile Printing



MYTEX

Code N° 187200

PRODUCT DESCRIPTION

Foil for partial hot transfer.

APPLICATION FIELDS

Partial transfer onto fabric and leather, pre-treated with appropriate adhesive.

APPLICATION PROCESS

ADHESIVE PRINTING:

TEXIFLOCK ST	Max 34 th/cm
TEXIFLOCK RT/RT-SF	Max 55 th/cm - Mesh 80
TEXIFLOCK E-FF	Max 43 th/cm
TEXIPLAST TRANSFER TRASP. PF	Max 34 th/cm
TEXIPLAST GT	Max 55 th/cm

Print the substrate with the appropriate adhesive, depending on the characteristics of the desired final effect. See the corresponding Technical Data Sheets of the above recommended adhesives.

TRANSFER:

Time	Max 15"
Temperature	Max 160°C
Pressure	2,5 – 4,0 bar
Peeling	Peel cold, after 8 h – 24 h

FEATURES:

Washing	<ul style="list-style-type: none"> • 30°C, programme for delicate clothes • Do not dry clean
---------	--

GENERAL FEATURES

- Metallized foil for partial hot transfer
- For continuous printing or pre-cut applications

APPLICATION:

Transfer conditions may vary, depending on the used equipment, the fabric type and the used adhesive. It is recommended not to exceed the maximum conditions indicated in the side table.

MYTEX OLOGRAMMA requires a transfer temperature not higher than 155°C, in order to prevent haze effect. The use of water based glues is recommended. Always peel cold, in order to obtain the best transfer fastness and brightness.

MYTEX LACCA follows the same application process. Check pressure and temperature of transfer well, in order to avoid unwanted colours of white under-bases. The use of water based glues is recommended. Always peel cold, in order to obtain the best transfer fastness and brightness.



Textile Printing



SPECIAL INSTRUCTIONS

- Always test the characteristics of the transfer, prior to start production.
- The above information is the result of previous knowledge and experience; it is neither a guarantee nor an assurance.
- Any possible post-treatment may influence the application results.

EQUIPMENT

Transferrable through manual, semi-automatic and automatic presses, and calenders.

STORAGE

- Away from direct sunlight
- At a temperature between 15 and 35°C

PACKAGING

See the corresponding colour chart.

SECURITY DATA SHEET

Available upon request.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.