



Textile Printing



TRANSFER FLOCK

Code N° 187100

PRODUCT DESCRIPTION

Textile polyamide fibres onto a polyester transparent substrate

APPLICATION FIELDS

Transfer on leather and fabrics, after treatment with an appropriate adhesive.

APPLICATION PROCESS

ADHESIVE PRINTING:

TEXIFLOCK ST	Max 34 th/cm
TEXIFLOCK E-FF	Max 43 th/cm

Print the substrate with the appropriate adhesive, depending on the characteristics of the desired final effect. See the corresponding Technical Data Sheets of the above recommended adhesives.

TRANSFER:

Time	20" – 25"
Temperature	170°C – 175°C
Pressure	2,5 – 4,0 bar
Peeling	Peel cold, after 8 h - 24 h

FORMATS/COLOURS:

FLOCK 1,0 mm	POLYESTER SHEETS: 50 x 80cm 46 colours + 5 fluorescents See the corresponding colour chart
--------------	--

FEATURES:

Washing	Max 40°C
---------	----------

The treated fabric has acceptable fastness values for 40°C washing with a programme for delicate clothes.

GENERAL FEATURES

- Good 40°C washing fastness
- For continuous printing onto fabric or leather
- Flock thickness 1 mm

APPLICATION:

Transferring conditions may vary, depending on the used equipment, the fabric type and the used adhesive.

Always peel cold, in order to obtain the best transfer fastness.

If the glue is not printed onto fabric/garment directly, but on to paper, remember to engrave the screen in its mirror image.



Textile Printing



SPECIAL INSTRUCTIONS

- Always test the characteristics of the transfer, prior to start production.
- After 12 months storage, after delivery, it is recommended to carefully check the product status through preliminary tests.
- The above information is the result of previous knowledge and experience; it is neither a guarantee nor an assurance.
- Any possible post-treatment may influence the application results.

EQUIPMENT

Transferrable through flat press or calender.

STORAGE

- Cool and dark place
- The product is sensitive to high temperatures and humidity

PACKAGING

- 50 sheets cardboard boxes

SECURITY DATA SHEET

Available upon request.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.